

2.08 PRIMAFLEX PVC M

Temperature range 0 °C bis 70 °C



Description

Universal hose made of two-ply elastic PVC with internal coated spring steel spiral.

Highly suitable for conveying gaseous media, vapors, dusts, powders, fibers, shavings, and liquids.

Available in our online shop

Properties

- Elastic
- Light
- Flexible
- Non-kinking
- Smooth interior
- Wall thickness: 0.70 mm.

Application ranges

Ventilation, Ventilation, Dust removal, Suction technology, PVC hoses, Suction hoses, dusts and powder, Suction hoses, air and gaseous media, Suction hoses, small shavings and solids, Plant engineering, Roof ventilation, Elastic hose, highly, Blower hose, Ventilation technology, Dust suction

Length

Standard length: 10 m.

Further informations

Standard color: grey, but also available in black or transparent.

Special colors: other RAL colors upon

TECHNICAL SPECIFICATIONS

Inner-Ø (mm)	Bending radius (mm)	Pressure (bar)	Vacuum (bar)	Weight (kg/m)	Length (m)	Article-No.
40	40	1,4	0,3	0,281	10	6053040
50	50	1,3	0,28	0,326	10	6053050
60	60	1,1	0,25	0,554	10	6053060
70	70	0,9	0,2	0,647	10	6053070
75	75	0,8	0,2	0,693	10	6053075
80	80	0,8	0,2	0,739	10	6053080
100	100	0,6	0,15	0,901	10	6053100
125	125	0,4	0,1	1,19	10	6053125
150	150	0,3	0,1	1,67	10	6053150
175	265	0,25	0,1	2,035	10	6053175
200	300	0,2	0,1	2,326	10	6053200
250	375	0,15	0,07	2,907	10	6053250
300	345	0,12	0,05	3,489	10	6053300
350	350	0,1	0,06	4,071	10	6053350
400	400	0,08	0,02	4,653	10	6053400
450	450	0,06	0,015	5,235	10	6053450
500	500	0,04	0,01	5,816	10	6053500