

2.02 PRIMAFLEX PVC SUPERELASTIC T

Temperature range 0 °C bis 85 °C



Description

The highly flexible PVC hose with strong tensile strength. Owing to a special manufacturing processes, it has a guide tunnel for cables or a further hose, e.g. for spraying and extraction devices. Ideally suited for industrial cleaning equipment.

Can also be fitted with patented, insulating tunnel solution

Available in our online shop

Properties

- Individual guide tunnel
- Highly flexible
- Fibre-reinforced
- Largely smooth on the inside
- Lightweight
- Durable/long useful life
- Kink-proof
- Particularly high tensile strength
- Vacuum resistant
- Tear-proof
- Good lye and acid resistance
- Good UV and ozone resistance
- Good chemical resistance
- Smallest of bending radiuses
- Pressure resistance
- Discharges electricity with earthing of the spiral
- Cadmium-free according to BGR 132

Application ranges

PVC hoses, suction hoses – small chips and solid matter, suction hoses – air and gaseous media, suction hoses – dusts and powder, suction technology

Length

Standard length: individual according to customer requirements

Further informations

Special colours: other RAL tones on request.

TECHNISCHE ANGABEN

Inner-Ø (mm)	Outer-Ø (mm)	Bending radius (mm)	Pressure (bar)	Vacuum (bar)	Weight (kg/m)	Length (m)	Price (€/m)	Article-No.
32	38	32	1,5	0,2	0,28	2,4 / 4	On request	After previous specifications
38	44	38	1,4	0,2	0,34	2,4 / 4	On request	

Technical specifications refer to base model „PVC Superelastic“. Other dimensions upon request.